

Deep Well Inspection Camera Kit

NM55HD series



- Ø55mm AHD camera head, sensor 1/3" CMOS ,1.3MP pixel
- Ø7mm x 100m flexible cable with depth counter function
- 32G USB flash storage device
- Video/audio recording & still image capture
- 720P video and AVI format
- 8800mA li-ion battery pack
- Keyboard for real time typewriting
- 10 inch HD color monitor
- With shoulder strap, easy to carry



- 10inch IPS screen
- DVR control box with video, audio recording and photography function
- LED brightness adjustable
- 8800mA li-ion battery
- HD 720P video ,MP4 format
- USB storage device (Standard 32G)
- USB keyboard to typewrite words

DVR Control unit




HD Control Box

- DVR control buttons
- keyboard for real time typewriting
- LED brightness adjustable
- Audio / Video recording & still image capture
- On/off microphone control button
- Video output



Camera Head

- Dimension: 55mm(D) X 80mm(L)
- Weight: 940g
- Waterproof: 10bar
- Led light: 8pcs high intensity Led
- Field of view: 90 degree
- AHD module, sensor 1/3" CMOS, 1.3MP pixel




Cable reel

- Oxygen free copper flexible cable 100m (Max 200m)
- Cable diameter $\varnothing 7\text{mm}$
- Depth counter function, display on the video



Battery pack & Charger

- 8800mA li-ion battery
- AC110V-240V 2A power charger
- Charging time 5 hours, working time 6 hours



Camera Standard Skid

- Diameter: 160mm



ABS Case

- Case size: 320 x 220 x 120mm
- Unit operating temperature: -10 to 50 degrees Celsius, RH 95% maximum
- Storage temperature: - 20 to 70 degrees Celsius, RH 95% maximum

Packing: • 1set/2cartons, 68.5*59*35cm&47*20*41cm, 32kg+10kg



Unit 17-03 & 17-04, Tower 1,
Faber Towers,
Jalan Desa Bahagia,
Taman Desa,
58100 Kuala Lumpur